



Specifications Noxion LED Panel Delta Pro V5 28W 3700lm - 830 Warm White | 120x30cm - UGR <19 - Sidelit - Philips Driver

[View Product](#)

## General Information

|                      |                                                                                               |
|----------------------|-----------------------------------------------------------------------------------------------|
| SKU                  | 257878                                                                                        |
| EAN                  | 8719157073882                                                                                 |
| Manufacturer Code    | 8719157073882                                                                                 |
| Brand                | Noxion                                                                                        |
| Manufacturer Name    | Noxion LED Panel Delta Pro V5.1 28W 3700lm 3000K 300*1200 (Philips Driver) UGR<19 Sidelit NDL |
| Budgetlight warranty | 6 Years                                                                                       |
| Average Lifetime (h) | 100000                                                                                        |
| Product Serie        | Delta Pro                                                                                     |

## Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Replaces (Watt)             | 2x36            |
| Wattage                     | 28W             |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 830 Warm White  |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |

|                        |                   |
|------------------------|-------------------|
| Luminous Flux (Lumen)  | 3700lm            |
| Lumen per watt         | 132               |
| IP-rating              | IP20              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Fixture Connection     | Push Terminal     |
| Finish of Reflector    | Frosted           |
| Power factor           | >0.90             |
| Product Type Category  | LED Panel         |

## Fixture Information

|                       |                    |
|-----------------------|--------------------|
| Mounting Method       | Recessed           |
| Unified Glare Rating  | < 19 - For offices |
| Optical Cover         | PS (Polystyrene)   |
| Operating Temperature | -20 to +40         |
| Emergency Lighting    | No Emergency Unit  |
| Colour of the Fixture | White              |
| Housing               | Steel              |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 120x30cm |
| Length (mm)    | 1195     |
| Width (mm)     | 295      |
| Height (mm)    | 10       |

**Sensor Information**  **Guaranteed budget prices**  **Up to 7 years warranty**

Type of sensor



**Easy** return process

No Sensor



Long-life **LED solutions**